

Features:

- fiber-to-fiber optical gain of up to 30 dB
- output power of up to 15 dBm
- -3 dB optical gain bandwidth of up to 35 nm

Package: Butterfly (DBUT)





Additional & customized:

- PM fiber pigtails
- FC/APC terminated pigtails

**Specifications
(nominal stabilization temperature +25 °C)**

Parameter	Min.	Typ.	Max.
Forward current, mA	-	-	300
Forward voltage, V	-	-	2.3
Output optical power, dBm	-	-	15.0
Central wavelength λ_c , nm	-	1060	-
-3 dB optical gain bandwidth, nm	-	35	-
Gain ripple, dB	-	< 0.1	-
Small signal gain, dB	-	-	30
Polarization dependent gain, dB	-	>10	-

PERFORMANCE EXAMPLES



The following part numbers should be used when **ordering**:

SOA-532-(a)-(b),
where:

- (a) – package type (DBUT),
- (b) – fiber type (SM or PM).

Example: SOA-532-DBUT-SM.

All specifications are subject to change without notice.

Continues on next page →

Performance examples (continued)

POWER BOOSTER PERFORMANCE EXAMPLES
 Output spectra at $P_{input}=2.0mW$, spectral $FWHM_{input}=0.08nm$

